

Application Note: AN10000

How to perform 64 bit arithmetic operations

This application note is a short how-to on programming/using the xTIMEcomposer tools. It shows how to perform 64 bit arithmetic operations.

Required tools and libraries

This application note is based on the following components:

- xTIMEcomposer Tools - Version 14.0.0

Required hardware

Programming how-tos are generally not specific to any particular hardware and can usually run on all XMOS devices. See the contents of the note for full details.

1 How to perform 64 bit arithmetic operations

The natural word length on the xCORE is 32 bits and it is usually fastest to operate with 32 bit integer types (e.g. `int` or `long`). For some algorithms wider integer types may be required. To address this the C and XC compilers provide the `long long` integer type which is 64 bits wide. You can declare variables of type `long long` as follows:

```
long long x; // Signed 64 bit integer.
```

A decimal integer constant that doesn't fit in a `long long` will have type `long long`. You can force a constant to have `long long` type using the LL and ULL suffixes:

```
f(123LL); // Constant has type long long.  
g(42ULL); // Constant has type unsigned long long.
```

The xCORE provides a number of instructions intended to improve the performance of multi-word arithmetic. The compiler targets these instructions when 64 bit arithmetic operations are used. For example consider 64 bit addition:

```
long long add64(long long b, long long c) {  
    long long a = b + c;  
    return a;  
}
```

Without any special support for multi-word arithmetic this operation would require 5 instructions. By making use of `ladd` instruction (`long add`) which has carry-in and carry-out operands the compiler can reduce the number of xCORE instructions required to 2.

The xCORE also provides instructions to improve the performance of multi-word addition, subtraction, multiplication and division.