

# UART library

A software defined, industry-standard, UART (Universal Asynchronous Receiver/Transmitter) library that allows you to control a UART serial connection via the xCORE GPIO ports. This library is controlled via C using the XMOS multicore extensions.

## Features

- UART receive and transmit
- Supports speeds up to 10MBit/s
- Half-duplex mode (applicable to RS485)
- Efficient multi-uart mode for implementing multiple connections

## Resource Usage

This following table shows typical resource usage in some different configurations. Exact resource usage will depend on the particular use of the library by the application.

Configuration	Pins	Ports	Clocks	Ram	Logical cores
Standard TX	1	1	0	~1.0K	0
Standard TX (buffered)	1	1	0	~1.3K	≤ 1
Standard RX	1	1	0	~1.5K	≤ 1
Fast/streaming TX	1	1	0	~0.2K	1
Fast/streaming RX	1	1	0	~0.2K	1
Multi-UART TX (8 UARTs)	8	1	0	~3.0K	1
Multi-UART RX (8 UARTs)	8	1	0	~3.4K	1
Half Duplex	1	1	0	~1.9K	1

## Software version and dependencies

This document pertains to version 3.1.0 of this library. It is known to work on version 14.2.3 of the xTIMEcomposer tools suite, it may work on other versions.

This library depends on the following other libraries:

- lib\_gpio (>=1.1.0)
- lib\_logging (>=2.1.0)
- lib\_xassert (>=3.0.0)